**IEEE** *Xplore*

Home | Login | Logout | Access Information | Alerts |

**Welcome United States Patent and Trademark Office**

**Search Session History**          BROWSE          SEARCH          IEEE XPLORE GUIDE

**Fri, 10 Jun 2005, 5:39:21 PM EST**

**Search Query Display**

[                                                                        ]

[ Run Search ]  [ Reset ]

**Recent Search Queries**

Edit an existing query or compose a new query in the Search Query Display.

**Select a search number (#) to:**

- Add a query to the Search Query Display
- Combine search queries using AND, OR, or NOT
- Delete a search
- Run a search

#1  ( ( optical power detection<in>metadata ) <and> ( level adjustment<in>metadata ) ) <and> (pyr >= 1950 <and> pyr <= 2001)

#2  ( ( optical power detection<in>metadata ) ) <and> (pyr >= 1950 <and> pyr <= 2001)

#3  ( ( optical power <in>metadata ) ) <and> (pyr >= 1950 <and> pyr <= 2001)

#4  ( ( optical power monitor<in>metadata ) ) <and> (pyr >= 1950 <and> pyr <= 2001)

#5  ( ( optical power monitor<in>metadata ) ) <and> (pyr >= 1950 <and> pyr <= 2001)

#6  ( ( optical power monitor<in>metadata ) ) <and> (pyr >= 1950 <and> pyr <= 2001)

#7  ( ( optical power monitor<in>metadata ) ) <and> (pyr >= 1950 <and> pyr <= 2001)

#8  optical power measurement<and>wdm <and> (pyr >= 1950 <and> pyr <= 2001)

#9  optical power measurement<and>wdm <and> (pyr >= 1950 <and> pyr <= 2001)

#10  optical power measurement<and>wdm <and> (pyr >= 1950 <and> pyr <= 2001)

#11  (optical power <and>wdm <and>noise detection<and> (pyr >= 1950 <and> pyr <= 2001)<IN>metadata)

#12  (optical power <and>wdm <and>noise level<and> (pyr >= 1950 <and> pyr <= 2001)<in>metadata)

#13  (optical receiverr <and>wdm <and>noise level<and> (pyr >= 1950 <and> pyr <= 2001)<in>metadata)

#14  (optical receiver <and>wdm <and>noise level<and> (pyr >= 1950 <and> pyr <= 2001)<in>metadata)

#15  (optical receiver <and>wdm <and>noise level<and> (pyr >=

1950 <and> pyr <= 2001)<in>metadata)

#16   (optical receiver <and>wdm <and>noise level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#17   (optical receiver <and>error detection <and>noise level<and>
(pyr >= 1950 <and> pyr <= 2001)<in>metadata)

#18   (optical receiver <and>error <and>noise level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#19   (optical receiver <and>error <and>noise level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#20   (optical receiver <and>error <and>noise level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#21   (optical receiver <and>error <and>noise level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#22   (optical receiver <and>error <and>noise level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#23   (optical receiver <and>error <and>threshold level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#24   (optical receiver <and>error <and>threshold level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#25   (optical receiver <and>error <and>threshold level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#26   (optical receiver <and>error <and>threshold level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#27   (optical receiver <and>error <and>threshold level<and> (pyr >=
1950 <and> pyr <= 2001)<in>metadata)

#28   (optical receiver <and>adaptive threshold <and> (pyr >= 1950
<and> pyr <= 2001)<in>metadata)

#29   (optical receiver <and>adaptive threshold <and> (pyr >= 1950
<and> pyr <= 2001)<in>metadata)

#30   (optical receiver <and>adaptive threshold <and> (pyr >= 1950
<and> pyr <= 2001)<in>metadata)

#31   (optical receiver <and>adaptive threshold <and> (pyr >= 1950
<and> pyr <= 2001)<in>metadata)

Clear Session History

Help    Contact Us    Privacy & :

Indexed by
Inspec